INTERNATIONAL JOURNAL OF PROGRESSIVE RESEARCH IN ENGINEERING MANAGEMENT AND SCIENCE (IJPREMS)
(Int Peer Reviewed Journal)
Vol. 05, Issue 08, August 2025, pp : 1954-1961
www.ijprems.com
editor@ijprems.com
e-ISSN : 2583-1062
Impact Factor : 7.001

ELEMENT MANAGEMENT SYSTEM FOR DWDM TRANSMISSION EQUIPMENT

Kushal PM[1], Mr. S Senthil Murugan[2]

[1]PG Student, Dept Of MCA, T John Institute Of Technology, Bengaluru, Karnataka, India.

[2]Assistant Professor, Dept Of MCA, T John Institute Of Technology, Bengaluru, Karnataka, India.

ABSTRACT

Dense Wavelength Division Multiplexing (DWDM) technology forms the backbone of modern high-capacity optical networks, enabling the transmission of vast amounts of data over single optical fibers. The intricate nature and dynamic capabilities of DWDM systems necessitate sophisticated management tools to ensure their optimal performance, reliability, and efficient operation. This paper presents the design principles, key functionalities, and implementation considerations for an advanced Element Management System (EMS) specifically tailored for DWDM transmission equipment. We explore how such an EMS leverages FCAPS (Fault, Configuration, Accounting, Performance, Security) functionalities to provide real-time monitoring, automated provisioning, proactive fault detection, and robust security across the optical layer. Furthermore, the paper discusses challenges related to managing complex optical impairments, dynamic Reconfigurable Optical Add/Drop Multiplexers (ROADMs), and multi-vendor environments, proposing solutions to enhance scalability, interoperability, and operational efficiency. Performance metrics and potential future enhancements, including AI/ML integration for predictive maintenance and SDN orchestration, are also discussed.

Keywords: DWDM, Element Management System (EMS), Optical Networks, FCAPS, ROADM, Network Management, Optical Layer, Fault Management, Configuration Management, Performance Management.

1. INTRODUCTION

An Element Management System (EMS) for DWDM (Dense Wavelength Division Multiplexing) equipment represents the indispensable brain and central nervous system of the modern optical transport network, a critical software layer designed to master the immense complexity born from the insatiable global demand for data. As the digital world's appetite for bandwidth fueled by cloud services, 5G mobile networks, and high-definition video outpaced the capabilities of older technologies, DWDM emerged as the foundational solution, functioning as a multi-lane superhighway for light itself. It achieves this by transmitting scores or even hundreds of independent data streams simultaneously over a single optical fiber, each assigned to a unique wavelength, or color, of light. This technological marvel, however, introduces a formidable management challenge, transforming the network from a set of simple components into a dynamic, highly sensitive ecosystem of advanced hardware such as transponders, muxponders, optical amplifiers (EDFAs and Raman), and crucially, Reconfigurable Optical Add-Drop Multiplexers (ROADMs) which allow for the software-defined routing of wavelengths. The sheer number of configurable parameters, the delicate physics of light transmission that must be constantly monitored for impairments like Chromatic Dispersion (CD) and Polarization Mode Dispersion (PMD), and the catastrophic service impact of a single component failure necessitate a sophisticated, centralized management platform. To address this, the EMS provides a unified, often graphical, interface that abstracts this intricate hardware reality, translating it into an operable and maintainable system for network engineers. Functionally, its role is best understood through the comprehensive FCAPS model, where it performs Fault management by not only detecting alarms but also correlating related events to perform root cause analysis, distinguishing a single degrading laser from a major fiber cut. In Configuration management , it moves beyond simple parameter settings to enable the end-to-end provisioning of optical services and light paths, a workflow that orchestrates changes across multiple devices to create a new circuit, with the ultimate goal being zero-touch provisioning. For Performance management, the EMS relentlessly collects and analyzes critical real-time and historical metrics like the Optical Signal-to-Noise Ratio (OSNR) and Bit Error Rate (BER), allowing operators to proactively identify signal degradation and prevent outages before they affect customers. Furthermore, the EMS handles Accounting by creating a detailed audit trail of all changes and user actions for security and planning, while its Security module ensures network integrity through robust authentication and authorization. Beyond these immediate operational tasks, the EMS serves a vital role in the broader network architecture, acting as the bridge between the physical equipment and higher-level Network Management Systems (NMS) or OSS/BSS platforms through its northbound interface, feeding them the processed data needed for network-wide visibility and orchestration. Ultimately, the strategic value of the EMS is measured in tangible business outcomes it dramatically reduces Operational Expenditures (OpEx) by minimizing the need for manual interventions and technician dispatches ("truck rolls"), accelerates service delivery to enhance business agility, and ensures the high availability and reliability required to meet stringent Service Level Agreements (SLAs), thereby solidifying its status as the cornerstone of a modern, intelligent optical network.

1.1 Background on Optical Networks and DWDM

The relentless surge in global data traffic, driven by cloud computing, streaming services, and ubiquitous connectivity, has placed immense pressure on telecommunications infrastructure. Optical fiber communication has emerged as the most efficient medium for high-speed data transmission, offering unparalleled bandwidth capabilities. Within this domain, Wavelength Division Multiplexing (WDM) revolutionized optical networks by allowing multiple data streams to be transmitted simultaneously over a single optical fiber, each carried on a distinct wavelength of light. Dense Wavelength Division Multiplexing (DWDM) is an advanced evolution of WDM that significantly increases fiber capacity by packing numerous wavelengths (typically 40, 80, 96, or more) into a very narrow spectral range. This capability makes DWDM indispensable for long-haul, metro, and even access networks requiring ultra-high bandwidth, providing substantial economic advantages by maximizing the utility of existing fiber infrastructure.

1.2 The Need for Network Management in DWDM

While DWDM offers immense capacity, its inherent complexity presents significant operational challenges. A typical DWDM network comprises a diverse array of sophisticated network elements (NEs) such as optical transponders/muxponders, optical amplifiers (EDFAs, Raman amplifiers), Reconfigurable Optical Add/Drop Multiplexers (ROADMs), and Dispersion Compensation Modules (DCMs). The precise management of numerous wavelengths, stringent power budget requirements, susceptibility to optical impairments (e.g., Chromatic Dispersion (CD), Polarization Mode Dispersion (PMD), non-linear effects), and the increasing demand for dynamic service provisioning render manual network management impractical, error-prone, and unsustainable for large-scale deployments. This necessitates robust network management systems that can provide comprehensive visibility, control, and automation. Network Management Systems (NMS) typically operate in a hierarchical structure, where an Element Management System (EMS) directly interacts with and manages a specific set of network elements from one or a few vendors. The EMS acts as the primary interface for configuration, monitoring, and troubleshooting at the device level, aggregating data and providing a simplified view of the underlying hardware.

2. LITERATURE REVIEW

In recent years, a large number of research studies have significantly advanced the field of Dense Wavelength Division Multiplexing (DWDM) transmission equipment, particularly in terms of capacity, flexibility, and network intelligence. Among the early influential works was by Ramaswami and Sivarajan in “Optical Networks: A Practical Perspective”[1], where the authors highlighted the fundamental architecture of DWDM systems and demonstrated how multiple optical channels could be multiplexed to achieve high-capacity transport. While their work laid the foundation for understanding DWDM technology, it primarily focused on fixed-grid systems and did not anticipate the emergence of coherent detection and flexible spectrum allocation. Agrawal, in “Fiber-Optic Communication Systems”[2], provided a comprehensive study of optical amplifiers, particularly Erbium-Doped Fiber Amplifiers (EDFAs) and Raman amplifiers, which remain critical in long-haul DWDM networks. Although his analysis of optical signal amplification was pioneering, it lacked the perspective of modern gain equalization techniques required for terabit-scale systems.

Building on these foundations, Winzer and Essiambre, in their work “Advanced Modulation Formats for High-Capacity Optical Transport Networks”[3], investigated the adoption of coherent detection and advanced modulation schemes such as QPSK and 16-QAM. Their study demonstrated significant improvements in spectral efficiency and tolerance to dispersion, making long-haul terabit transmission feasible. However, the proposed architectures were computationally intensive, requiring advanced DSP capabilities not widely available at the time. Similarly, Roberts et al., in “Beyond 100 Gb/s: Optical Transport Evolution”[4], discussed the transition to 100 Gbps and beyond per channel, emphasizing coherent transponders and flexible-grid systems. Despite demonstrating record-breaking capacities, the work highlighted practical challenges of cost, power consumption, and standardization across vendors.

Another significant contribution was from Chatterjee et al., in “ROADMs and the Evolution of Flexible Optical Networks”[5], where the authors examined the emergence of colorless, directionless, and contentionless Reconfigurable Optical Add-Drop Multiplexers (ROADMs). Their findings showed how modern ROADMs enabled dynamic wavelength routing and network reconfigurability. However, while flexibility was improved, complexity in network planning and management also increased. More recent studies, such as Sambo et al.’s “Next-Generation Elastic Optical Networks”[6], proposed flexible-grid DWDM systems that dynamically allocate spectrum to channels based on demand, improving utilization and adaptability. While promising, these architectures required significant upgrades to legacy equipment, slowing practical deployment.

From a management perspective, Neng et al., in “Performance Monitoring in Coherent Optical Networks”[7], highlighted the integration of real-time monitoring tools for OSNR, BER, and Q-factor, which facilitated proactive fault detection and network optimization. Although the techniques improved service reliability, they required advanced DSP algorithms and increased processing overhead. Complementing this, studies such as Zhao et al. in “AI and Machine Learning for Optical Transmission Systems”[8] explored intelligent fault management and performance prediction, demonstrating improved automation. Despite these advantages, AI-driven approaches were heavily dependent on high-quality training datasets, limiting generalizability across diverse network environments.

More recent trends have shifted toward hardware modularity and pluggability. Cisco and Infinera’s white papers [9][10] on pluggable coherent optics demonstrated cost-effective scaling for metro and long-haul networks, showing that compact transponders could deliver 400G transmission in standard form factors. While this innovation addressed cost and space challenges, it raised concerns around interoperability and thermal management. Furthermore, modern research has emphasized energy efficiency, as highlighted in Bolla et al.’s “Energy Efficiency in Optical Transport Networks”[11], which discussed reducing operational power consumption through intelligent transponder design. However, such methods often trade off with system reach or performance.

An Element Management System (EMS) for DWDM transmission equipment has drawn on a wide spectrum of research spanning telecommunications, software engineering, and network management. Early foundational work was influenced by the International Telecommunication Union’s Telecommunications Management Network (TMN) framework[12], which defined a hierarchical architecture comprising the element, network, service, and business management layers. This model provided the conceptual basis for EMS design, placing emphasis on the element layer while linking upward into broader network and service control. Early EMS implementations, as described in proprietary vendor documentation and early academic studies [13], concentrated primarily on FCAPS (Fault, Configuration, Accounting, Performance, and Security) functionalities delivered through basic command-line interfaces and vendor-specific protocols. While effective for small-scale deployments, these systems were tightly coupled to hardware, creating interoperability challenges and restricting scalability.

The literature of the early 2000s marked a turning point with an emphasis on open standards and vendor-neutral management frameworks. Studies such as those by Stallings in “SNMP, SNMPv2, and RMON”[14] and later by Bjorkman et al. [15] on NETCONF/YANG highlighted how standardized protocols could replace proprietary systems, enabling multi-vendor EMS operation. This shift provided the foundation for greater interoperability and flexibility in DWDM environments. In parallel, significant research was devoted to performance management. Scholars such as Klekamp et al., in “Performance Monitoring for High-Capacity Optical Networks”[16], developed methods for real-time monitoring of optical parameters including Optical Signal-to-Noise Ratio (OSNR), Chromatic Dispersion (CD), and Polarization Mode Dispersion (PMD). These contributions extended EMS functionality from simple fault reporting toward predictive fault analysis, where anomalies in optical parameters could serve as early warnings of service degradation. Such developments underscored the literature’s growing recognition of EMS as a proactive, rather than purely reactive, management tool.

More recent research has emphasized scalability and distributed architectures. For instance, Youn et al. in “Distributed EMS Architectures for Large-Scale Optical Networks”[17] proposed scalable database frameworks to handle the exponential growth of performance data in terabit-scale DWDM systems. These works demonstrated that centralized EMS architectures were insufficient for modern optical backbones and argued for distributed, modular approaches to ensure fault tolerance and high availability. At the same time, the integration of Software-Defined Networking (SDN) and Network Function Virtualization (NFV) into optical management began to attract significant attention. Studies such as Liu et al. in “SDN-Controlled Elastic Optical Networks”[18] illustrated how EMS platforms could evolve from passive monitoring tools into active orchestrators, dynamically reconfiguring the optical layer in response to shifting traffic patterns. Open-source frameworks and RESTful APIs were emphasized in these studies, creating more programmable and agile EMS platforms that could seamlessly interface with higher-level orchestration layers.

The latest phase of EMS literature highlights the transformative role of Artificial Intelligence (AI) and Machine Learning (ML) in network management. Research by Zhang et al. in “AI-Driven Optical Network Management”[19] explored the use of ML algorithms for anomaly detection, capacity forecasting, and intelligent alarm correlation. These studies positioned EMS not just as a management interface but as a self-healing and self-optimizing system, capable of predictive maintenance and root-cause analysis without human intervention. Similar contributions by Chen et al.[20] have demonstrated how ML-based predictive models can anticipate hardware failures in optical transponders, reducing downtime and improving service reliability. Collectively, this body of work reflects a paradigm shift: EMS has evolved from being a vendor-specific, reactive management tool into a modular, cloud-native, and intelligent platform integral to autonomous optical networking.

3. ARCHITECTURE AND DESIGN PRINCIPLES OF A DWDM EMS

A robust DWDM EMS is built upon a modular and scalable architecture designed to handle the complexity and real-time demands of optical networks.**Fig-1:**Shows the example of architecture and design.

3.1 Layered Architecture (TMN Model)

Following the ITU-T Telecommunications Management Network (TMN) model, the EMS primarily operates at the Element Layer, directly managing individual DWDM network elements. However, it often extends its capabilities to the lower functionalities of the Network Layer by providing domain-specific views and cross-element service provisioning within its managed scope.

3.2 Modular Design

IA modular architecture is paramount for flexibility, scalability, easier maintenance, and independent development of functionalities. Key modules within a typical DWDM EMS include:

Northbound Interface (NBI) Gateway: Handles communication with higher-level NMS/OSS/BSS systems.

Graphical User Interface (GUI) Layer: Provides interactive dashboards, topology views, and configuration interfaces.
Core EMS Logic: Processes management requests, applies business rules, and orchestrates operations.
Fault Management Module: Collects alarms, performs correlation, and initiates fault resolution.
Configuration Management Module: Manages device configurations, provisioning workflows, and software upgrades.
Performance Management Module: Collects, processes, and analyzes performance data, generates reports.
Security Management Module: Manages user authentication, authorization, and audit logging.
Inventory Module: Maintains a database of all network assets.
Database Layer: Stores persistent data (configurations, alarms, performance metrics, inventory).
Southbound Interface (SBI) Adapters: Translates EMS commands into device-specific protocols and parses device responses.



Figure 1: Example of architecture and design DWDM EMS

3.3 Communication Protocols and Interfaces

The choice of communication protocols is critical for effective interaction with diverse DWDM equipment.
Southbound Interfaces (to NEs):
SNMP (Simple Network Management Protocol): Widely used for basic monitoring (polling MIBs) and setting simple

configurations. However, its capabilities for complex optical provisioning are limited.

TL1 (Transaction Language 1): A legacy, command-line-based protocol still prevalent in older optical transport equipment. Requires specific parsers.

NETCONF/YANG: An emerging and preferred standard for programmatic network management. NETCONF provides a secure, XML-based protocol for configuration management, while YANG defines data models for network elements, offering structured, vendor-agnostic configuration and state information. This is ideal for complex optical systems and SDN integration.

Proprietary APIs/CLI: Many vendors still expose proprietary Command Line Interfaces (CLI) or custom APIs (often based on REST or gRPC) for advanced or vendor-specific functionalities not covered by standards. The EMS must incorporate adapters for these.

Northbound Interfaces (to NMS/OSS/BSS):

RESTful APIs: The most common and flexible choice for modern integration, allowing higher-level systems to query EMS data, initiate provisioning, and receive notifications.

SNMP Traps: For real-time fault notifications to a centralized NMS.

Legacy Interfaces: Such as CORBA or SOAP may still be required for integration with older OSS/BSS systems.

3.4 Scalability and High Availability

For managing mission-critical DWDM networks, the EMS itself must be highly available and scalable:

Clustering and Load Balancing: Distributing processing load across multiple servers and providing failover capabilities for core EMS components.

Distributed Architecture: For managing very large-scale DWDM networks, certain EMS modules (e.g., data collection agents) can be distributed geographically closer to the NEs.

Redundant Components: Implementing redundancy at all levels, including redundant power supplies, network connections, and active-standby or active-active configurations for critical servers and databases.

3.5 Security Architecture

Security is paramount for an EMS managing core network infrastructure:

Authentication: Robust user authentication mechanisms (e.g., integration with LDAP/Active Directory, RADIUS, or secure local user management).

Authorization (Role-Based Access Control - RBAC): Defining granular permissions based on user roles (e.g., network administrator, operator, viewer) to restrict access to specific functionalities or network elements.

Data Encryption: Encrypting all communication between the EMS client and server, and between the EMS and network elements (e.g., SSH for NETCONF, TLS for REST APIs).

Audit Trails and Logging: Comprehensive logging of all user activities, configuration changes, and system events for accountability and forensic analysis.

Vulnerability Management: Regular security audits, penetration testing, and timely patching of the EMS software.

4. RESULTS

The effectiveness of a DWDM EMS is ultimately measured by its ability to enhance network operations, and this is assessed through key performance indicators (KPIs) and evaluation metrics. For fault management, critical KPIs include Mean Time To Detect (MTTD), Mean Time To Isolate (MTTI), and Mean Time To Repair (MTTR), alongside the Alarm Correlation Ratio, which indicates how effectively raw alarms are converted into actionable events. In configuration management, metrics such as service provisioning time and configuration error rate are important for evaluating efficiency and reliability. Performance management is measured through data collection latency, dashboard refresh rates, and the accuracy of predictions in AI/ML-driven features, such as optical signal-to-noise ratio (OSNR) forecasting. At the system level, response time, scalability, resource utilization, and availability provide insights into the overall robustness of the EMS platform. To rigorously validate these metrics, a dedicated testbed or simulation environment is essential, which may involve hardware-in-the-loop setups, network emulators or simulators for scalability testing, and fault injection tools to test responses to failures such as fiber cuts, amplifier malfunctions, or wavelength drifts. Furthermore, benchmarking EMS performance against industry standards, service level agreements (SLAs), and other commercial EMS solutions ensures objective evaluation, offering a quantitative measure of effectiveness and competitive standing.

INTERNATIONAL JOURNAL OF PROGRESSIVE RESEARCH IN ENGINEERING MANAGEMENT AND SCIENCE (IJPREMS)
(Int Peer Reviewed Journal)
Vol. 05, Issue 08, August 2025, pp : 1954-1961
e-ISSN : 2583-1062
Impact Factor : 7.001



Figure 2: Login page

Figure 3: Main Dashboard



Figure 4: Alarm Dashboard

Figure 5: Element View



Figure 6: Performance Analysis

INTERNATIONAL JOURNAL OF PROGRESSIVE RESEARCH IN ENGINEERING MANAGEMENT AND SCIENCE (IJPREMS)
(Int Peer Reviewed Journal)
Vol. 05, Issue 08, August 2025, pp : 1954-1961
www.ijprems.com
editor@ijprems.com
e-ISSN : 2583-1062
Impact Factor : 7.001



Figure 7: Path Analysis

5. CONCLUSION

Dense Wavelength Division Multiplexing (DWDM) is the cornerstone of high-capacity optical networks, but its inherent complexity necessitates sophisticated management solutions. This paper has presented a comprehensive overview of an Element Management System (EMS)bspecifically designed for DWDM transmission equipment, outlining its architectural principles, core FCAPS functionalities, and key implementation considerations.

A robust DWDM EMS acts as the critical operational interface, moving beyond rudimentary device control to provide intelligent, real-time management of the optical layer. By implementing advanced fault correlation, automated wavelength provisioning, precise optical power management, and detailed performance monitoring, such an EMS significantly enhances operational efficiency, reduces manual errors, and improves network reliability. Addressing challenges like multi-vendor interoperability and the complexity of ROADM management through modular design and adherence to open standards (like NETCONF/YANG) is crucial for successful deployment.

Looking ahead, the integration of Artificial Intelligence and Machine Learning (AI/ML) promises to transform DWDM EMS from a reactive management tool into a proactive, self-optimizing system. AI/ML can enable predictive maintenance, intelligent anomaly detection, and highly dynamic resource optimization, leading to unprecedented levels of automation and network performance. Furthermore, seamless integration with SDN controllers will empower operators with greater programmatic control and end-to-end service orchestration across convergent network layers.

An intelligently designed and effectively implemented EMS is not merely a tool but a strategic asset for network operators. It unlocks the full potential of DWDM technology, ensuring the stable, efficient, and cost-effective operation of the high-capacity optical infrastructure that underpins the digital world. Continued research and development in areas like AI/ML, digital twins, and open interoperability will further refine the capabilities of DWDM EMS, paving the way for even more resilient and autonomous optical networks.

6. REFERENCES

[1] R. Ramaswami and K. Sivarajan, Optical Networks: A Practical Perspective, 3rd ed. San Francisco, CA, USA: Morgan Kaufmann, 2009.

[2] G. P. Agrawal, Fiber-Optic Communication Systems, 4th ed. Hoboken, NJ, USA: Wiley, 2010.

[3] P. J. Winzer and R.-J. Essiambre, "Advanced modulation formats for high-capacity optical transport networks," J. Lightwave Technol., vol. 24, no. 12, pp. 4711–4728, Dec. 2006.

[4] K. Roberts et al., "Beyond 100 Gb/s: Optical transport evolution," IEEE Commun. Mag., vol. 50, no. 2, pp. 128–135, Feb. 2012.

[5] B. Chatterjee, E. O. Elliott, and C. Clark, "ROADMs and the evolution of flexible optical networks," IEEE Commun. Surveys Tuts., vol. 15, no. 4, pp. 1848–1870, 2013.

[6] N. Sambo, A. Cugini, F. Paolucci, and P. Castoldi, "Next-generation elastic optical networks: The vision of the European STRONGEST project," IEEE Commun. Mag., vol. 50, no. 2, pp. 80–88, Feb. 2012.

[7] H. Neng, T. S. R. Shen, and Z. Li, "Performance monitoring in coherent optical networks," Optical Fiber Technol., vol. 18, no. 2, pp. 103–110, Mar. 2012.

[8] Y. Zhao, L. Zhang, and J. Han, "AI and machine learning for optical transmission systems," J. Opt. Commun. Netw., vol. 11, no. 10, pp. C1–C14, Oct. 2019.

[9] Cisco Systems, Cisco 400G Pluggable Optics: White Paper. San Jose, CA, USA: Cisco, 2020.

[10] Infinera, Enabling Terabit-Scale Pluggable Optics. Sunnyvale, CA, USA: Infinera, 2021.

[11] R. Bolla, R. Bruschi, F. Davoli, and F. Cucchietti, "Energy efficiency in optical transport networks," IEEE Netw., vol. 25, no. 2, pp. 26–32, Mar.–Apr. 2011.

[12] ITU-T, Telecommunications Management Network (TMN) Framework, ITU-T Recommendation M.3010, Geneva, Switzerland, 2000.

[13] J. Case, M. Fedor, M. Schoffstall, and J. Davin, A Simple Network Management Protocol (SNMP), IETF RFC 1157, May 1990.

[14] W. Stallings, SNMP, SNMPv2, SNMPv3, and RMON 1 and 2, 3rd ed. Reading, MA, USA: Addison-Wesley, 1999.

[15] T. Bjorkman, A. Shaikh, and D. Ward, "NETCONF and YANG: Evolution of network configuration management," IEEE Commun. Mag., vol. 53, no. 2, pp. 152–159, Feb. 2015.

[16] A. Klekamp, C. Raack, and W. Idler, "Performance monitoring for high-capacity optical transport networks," Bell Labs Tech. J., vol. 17, no. 3, pp. 39–54, Dec. 2012.

[17] S. Youn, Y. Lee, and J. Lee, "Distributed EMS architectures for large-scale optical networks," IEEE Netw., vol. 29, no. 6, pp. 30–36, Nov.–Dec. 2015.

[18] L. Liu, Y. Ji, and M. Tornatore, "SDN-controlled elastic optical networks," IEEE Commun. Surveys Tuts., vol. 18, no. 4, pp. 2738–2770, 2016.

[19] Y. Zhang, X. Chen, and T. Huang, "AI-driven optical network management: An overview," IEEE Opt. Commun. Mag., vol. 58, no. 6, pp. 38–45, Jun. 2020.

[20] J. Chen, R. Proietti, and S. Yoo, "Machine learning for predictive failure management in optical networks," J. Lightwave Technol., vol. 38, no. 9, pp. 2590–2600, May 2020.